



▶ Polycom®
RMX® 1500/2000/4000
XML API Overview

Trademark Information

Polycom®, the Polycom “Triangles” logo, and the names and marks associated with Polycom’s products are trademarks and/or service marks of Polycom, Inc., and are registered and/or common-law marks in the United States and various other countries. All other trademarks are the property of their respective owners.

Patent Information

The accompanying product is protected by one or more U.S. and foreign patents and/or pending patent applications held by Polycom, Inc.

© 2012 Polycom, Inc. All rights reserved.

Polycom, Inc.
4750 Willow Road
Pleasanton, CA 94588-2708
USA

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Polycom, Inc. Under the law, reproducing includes translating into another language or format.

As between the parties, Polycom, Inc., retains title to and ownership of all proprietary rights with respect to the software contained within its products. The software is protected by United States copyright laws and international treaty provision. Therefore, you must treat the software like any other copyrighted material (e.g., a book or sound recording).

Every effort has been made to ensure that the information in this manual is accurate. Polycom, Inc., is not responsible for printing or clerical errors. Information in this document is subject to change without notice.

Table of Contents

Introduction.....	1
Contents of the RMX XML SDK	1
Types of Schemas	2
Common Schemas (Prefix common).....	2
Object Schemas (Prefix obj)	2
Transaction Schemas (Prefix trans)	2
Response Schemas (Prefix response_trans).....	3
The response_general Schema	3
Description of the Individual Schemas.....	4
Working with the RMX XML API	11
Communicating with the RMX XML API	11
XML Requests and Responses	11
The RMX XML API Internal XML Parser.....	12
Logging in to the MCU	12
The trans_mcu Schema	12
An XML Example	24
Keeping the Connection with the MCU Alive.....	26
Working with the Response and Transaction Schemas.....	26
Audio Muting a Participant - An XML Example	29
Transaction Processing.....	30
Polling for Data	32
Retrieving Channel Information for IP Participants.....	35
The Compression Mechanism.....	35
Sending XML requests in Compressed Format	35
Receiving XML responses from the MCU in Compressed Format.....	36

Introduction

RMX User workstations and other external systems are connected to the MCU via TCP/IP LAN connections using XML over HTTP. These external systems communicate with the MCU using the RMX XML API as a low level API.

The RMX XML API works as an internal web site on the MCU. The web site receives XML pages and sends the answer back in XML format. All requests and responses have schema formats. The syntax used for the XML API schemas is according to the W3C recommendation implemented in MS version 4 MSXML.

Copies of all the RMX XML API schemas are supplied in the **Schemas** folder in the RMX SDK. The XML API schemas are text files, and you can open them with any editor you want. Internet Explorer can be used to view the files in a convenient format.

This guide provides basic instructions for working with the RMX XML API. For more detailed information, refer to the RMX XML API Reference Guide. Contents of the RMX XML SDK

The RMX XML SDK consists of the following items:

- Copies of all of the RMX XML schemas (located in the **Schemas** folder).
- The Polycom XML Tracer application (located in the Tracer folder).
- Sample Scripts that can be used to communicate with an LDAP database (located in the External_Database_LDAP folder)
- Documentation (located in the Docs folder)

The **Docs** Folder contains the following documents:

- RMX XML API Release Notes V7.6.1
- RMX XML API Overview V7.6.1 (this document)
- Polycom RMX XML API V7.6.1 Reference (.chm file)
- MGC to RMX 2000 XML API Conferencing Comparison
- RMX 2000 External Database API Programmer's Guide
- Polycom XML Tracer User Guide V1_52
- Readme file

Types of Schemas

The schemas are divided to four categories, each with a different prefix, as follows:

Common Schemas (Prefix common)

The common schemas are like h files in C, and are included in other schemas. They contain definitions of elements that are common to multiple schemas. The common schemas are as follows:

- **common_obj** - This contains elements that are used by multiple object schemas.
- **common_obj_ip_span** - This contains elements that are used by multiple IP related schemas.
- **common_trans** - This contains elements that are used by multiple transaction schemas.
- **common_trans_obj** - This contains elements that are used by multiple transaction and object schemas.

Object Schemas (Prefix obj)

The object schemas describe the format and parameters of objects in the MCU, for example, conference or participant.

Transaction Schemas (Prefix trans)

The transaction schemas are used to retrieve the data of objects in the MCU (get requests), or to act on objects in the MCU (set requests). For example, the schema **trans_res_1** defines the XML format to create a conference, Entry Queue, SIP Factory, Meeting Room or Profile on the MCU, to update the properties of an Entry Queue, SIP Factory, Meeting Room or Profile, to define the default Entry Queue, and to remove the definition of the default Entry Queue.

The transaction schemas often contain other types of schemas, such as object schemas and common schemas. For example, the **trans_res_1** schema includes the **obj_reservation** schema, because it has to include the conference data when it is sent to start a conference.

The transaction schemas have a consistent pattern that demonstrates object oriented methodology, as follows:

1. The root element is the schema name.
2. The next element is the TRANS_COMMON_PARAMS element, which is similar to a base class. This element mainly describes the MCU on which the action is to operate, and the synchronization method to be used.
3. The next element is the ACTION element.
4. After this there are details of the individual actions that the transaction can make. For example, the actions in trans_res_1 are START (to create a conference, Entry Queue, SIP Factory, Meeting Room or Profile), UPDATE (to update the properties of an Entry Queue, SIP Factory, Meeting Room or Profile), SET_DEFAULT_EQ (to define the default Entry Queue) and CANCEL_DEFAULT_EQ (to remove the definition of the

default Entry Queue). For each action, there is a description of the parameters that must be specified in order to initiate the action.

Response Schemas (Prefix **response_trans**)

The response schemas describe the XML format returned by the XML API for the sent transactions.

The response schemas have a consistent pattern, as follows:

1. The root element is the schema name.
2. The next element is the return status for the transaction.
3. The next element is the ACTION element.
4. After this is a choice of the actions that this response answers, corresponding to the actions in the **trans_xxx** schema. Under each action there is a description of the returned data.

In general, each **trans_xxx** schema has a corresponding **response_trans_xxx** schema. However, although due to internal performance considerations the **trans_res** and **trans_conf** schemas were each split into two schemas (**trans_res_1** and **trans_res_2**, and **trans_conf_1** and **trans_conf_2**, respectively), there is only one response schema for each pair of transactions, (**response_trans_res** and **response_trans_conf**, respectively).

The **response_general** Schema

The **response_general** schema is returned when there is no response with data available, for example, when an invalid schema is sent.

Usually the **response_general** schema only contains a status which explains why the requested response was not sent. However, the schema optionally contains a TRANS_TOKEN element, which is used for asynchronous transactions for which the full response is not returned automatically, and an ACTION_TYPE element which identifies the type of request that was sent.

Description of the Individual Schemas

The RMX 1500/2000/4000 XML API developer's kit version 7.6.1 contains the following 143 schemas:

Schema	Description
common_obj	Contains elements that are used by multiple object schemas.
common_obj_ip_span	Contains elements that are used by multiple IP related schemas.
common_trans	Contains elements that are used by multiple transaction schemas.
common_trans_obj	Contains elements that are used by multiple transaction and object schemas.
obj_active_alarms_list	Holds a list of system alerts.
obj_active_directory	Holds information about the Active Directory. (Applicable from versions 7.5.0.J and 7.6)
obj_audit_file_summary_list	Holds a list of auditor file summaries.
obj_av_msg_service	Holds information about Conference and Entry Queue IVR Services.
obj_cards_list	Holds information about cards.
obj_cdr_full	Holds complete information about a CDR.
obj_cdr_summary_list	Holds summary information about a CDR.
obj_certificate_summary	Holds the information of a security certificate used by the RMX. (Applicable from versions 7.5.0.J and 7.6)
obj_certificate_summary_list	Holds a list of the information of a security certificate used by the RMX. (Applicable from versions 7.5.0.J and 7.6)
obj_cfg	Holds a list of system configuration flag names and values.
obj_collect_info	Contains elements used for the Information Collector. (Applicable from version 7.2)
obj_conf_summary_list	Holds summary information about conferences.
obj_conference	Holds detailed information about a conference.
obj_connection	Holds connection information for a user who is connected to the MCU.
obj_connections_list	Holds connection information for all users who are connected to the MCU.
obj_directory	Holds the contents of a directory, that is, a list of the names of the files and sub-directories in the directory.
obj_dongle_configuration	Mostly for internal use only, but also holds the number of licensed ports.
obj_dynamic_content_table	This schema contains the information of content resolution settings and content rate as a function of conference rates for content enhancements support. (Applicable from version 7.6.1)

Schema	Description
obj_dynamic_ip_service	Holds the dynamically changing parameters of an IP Service. The dynamically changing parameters are the parameters that are displayed by the Signaling Monitor.
obj_ethernet_settings	Holds information about a LAN port of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
obj_ethernet_settings_list	Holds information about all LAN ports of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
obj_exchange_cfg	Holds information about the connection to the Microsoft Exchange Server. (Applicable from version 6.0)
obj_faults_list	Holds a list of faults.
obj_force	Holds information about the arrangement of video windows on the endpoint screens, and information about which participants are forced to appear in specific windows.
obj_full_ip_service	Holds full information about an IP Network Service, that is, both the general parameters and the dynamically changing parameters.
obj_full_ip_service_list	Holds full information about all IP Network Services, that is, both the general parameters and the dynamically changing parameters.
obj_hot_backup	Contains the Hot Backup configuration parameters. (Applicable in version 4.6/4.7.x and from version 7.2)
obj_install_phase	Contains the parameters of a single software installation phase. (Applicable from version 6.0)
obj_install_phases_list	Contains a list of phases that are part of the software installation procedure. (Applicable from version 6.0)
obj_ip_service	Holds information about general parameters of an IP or Management Network Service.
obj_ip_service_list	Holds information about all IP or Management Network Services.
obj_isdn_srv	Holds information about an ISDN/PSTN Network Service.
obj_isdn_srv_list	Holds information about all ISDN/PSTN Network Services.
obj_lecture_mode	Holds Lecture Mode information.
obj_licensing_configuration	Holds license information.
obj_logger	Contains information about the Logger Configuration function (Applicable from version 7.6)
obj_log_file_summary_list	Holds a list of log file summaries.
obj_mcu_time	Holds the MCU time.
obj_ongoing_party	Holds information about a participant in a conference.
obj_oper_list	Holds information about all MCU users.
obj_operator	Holds information about an MCU user.

Schema	Description
obj_party	Holds information about a participant.
obj_recording_links_list	Holds a list of recording links.
obj_repeated	Contains a list of recurrent reservations values. (Applicable from version 4.0)
obj_res_summary_list	Holds summary information about Meeting Rooms, Entry Queues, SIP Factories and Profiles.
obj_reservation	Holds detailed information about a conference, Meeting Room, Entry Queue, SIP Factory or Profile.
obj_resolutions_set	Contains the decision array of video resolutions that are used for video conferences. (Applicable from version 7.0)
obj_rsrc_report	Holds a resource report for an RMX.
obj_rtm_isdn_span	Holds information about an ISDN/PSTN span.
obj_rtm_isdn_span_list	Holds information about all ISDN/PSTN spans.
obj_service	Holds a subset of the information about an ISDN/PSTN Network Service.
obj_snmp	Holds SNMP (Simple Network Management Protocol) details.
obj_tcp_dump	Contains elements used for the TCP dump Network Traffic Capture interface. (Applicable from version 7.2)
response_general	Returned when there is no response with data available, for example, when an invalid schema is sent. Usually the response_general schema only contains a status which explains why the requested response was not sent. However, the schema optionally contains a TRANS_TOKEN element, which is used for asynchronous transactions for which the full response is not returned automatically.
response_trans_active_alarms_list	Contains the response to the trans_active_alarms_list schema, which is used to retrieve system alerts.
response_trans_audit_file_summary_list	Contains the response to the trans_audit_file_summary_list schema, which is used to retrieve a list of auditor file summaries.
response_trans_av_msg_service	Contains the response to the trans_av_msg_service schema, which is used to manage a Conference or Entry Queue IVR Service.
response_trans_av_msg_service_list	Contains the response to the trans_av_msg_service_list schema, which is used to retrieve information about Conference and Entry Queue IVR Services.
response_trans_card	Contains the response to the trans_card schema, which is used to manage a card.
response_trans_cards_list	Contains the response to the trans_cards_list schema, which is used to retrieve details of all the cards in the MCU.
response_trans_cdr_full	Contains the response to the trans_cdr_full schema, which is used to retrieve the complete CDR information from the MCU.
response_trans_cdr_list	Contains the response to the trans_cdr_list schema, which is used to retrieve a list of CDR summaries from the MCU.
response_trans_certificate	Contains the response to the trans_certificate schema, which is used to send certificates to the RMX.

Schema	Description
response_trans_certificate_list	Contains the response to the trans_certificate_list schema, which is used to retrieve a list of certificates from the MCU. (Applicable from version 7.5.0.J and 7.6)
response_trans_certificate_request	Contains the response to the trans_certificate_request schema, which is used to create certificate requests.
response_trans_cfg	Contains the response to the trans_cfg schema, which is used to manage system configuration flags.
response_trans_conf	Contains the response to the trans_conf_1 or trans_conf_2 schemas, which are used to perform operations on conferences.
response_trans_conf_list	Contains the response to the trans_conf_list schema, which is used to retrieve a list of conference summaries.
response_trans_conferences_rsrc	This schema contains the response to the trans_conferences_rsrc schema, which is used to retrieve a list of conference resources. (Applicable from version 7.6.1)
response_trans_connections_list	Contains the response to the trans_connections_list schema, which is used to retrieve connection information about all users who are currently connected to the MCU.
response_trans_ethernet_settings	Contains the response to the trans_ethernet_settings schema, which is used to manage the LAN ports of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
response_trans_ethernet_settings_list	Contains the response to the trans_ethernet_settings_list schema, which is used to retrieve details of the LAN ports of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
response_trans_faults_list	Contains the response to the trans_faults_list schema, which is used to retrieve the full faults list.
response_trans_faults_list_short	Contains the response to the trans_faults_list_short schema, which is used to retrieve an abbreviated faults list, that is, a faults list without the asserts.
response_trans_hot_backup	Contains the response to the trans_hot_backup schema, which is used to retrieve and update the hot backup configuration. (Applicable in version 4.6/4.7.x and from version 7.2)
response_trans_ip_service	Contains the response to the trans_ip_service schema, which is used to manage an IP and Management Network Service.
response_trans_ip_service_list	Contains the response to the trans_ip_service_list schema, which is used to retrieve details of IP and Management Network Services.
response_trans_isdn_phone	Contains the response to the trans_isdn_phone schema, which is used to manage ISDN/PSTN phone number ranges.
response_trans_isdn_service	Contains the response to the trans_isdn_service schema, which is used to manage ISDN/PSTN Network Services.
response_trans_isdn_service_list	Contains the response to the trans_isdn_service_list schema, which is used to retrieve details of all ISDN/PSTN Network Services.
response_trans_log_file_list	Contains the response to the trans_log_file_list schema which is used to retrieve a list of log file summaries.

Schema	Description
response_trans_logger	Contains the response to the trans_logger schema, which is used to manage the Logger Configuration utility. (Applicable from version 7.6)
response_trans_mcu	Contains the response to the trans_mcu schema, which is used to log in and out of the MCU, to retrieve information from the MCU, and to perform configuration and file operations on the MCU.
response_trans_oper_list	Contains the response to the trans_oper_list schema, which is used to retrieve information about all defined RMX users.
response_trans_operator	Contains the response to the trans_operator schema, which is used to manage an RMX user.
response_trans_party	Contains the response to the trans_party schema, which is used to retrieve information about a participant in a conference.
response_trans_recording_links_list	Contains the response to the trans_recording_links_list schema, which is used to manage recording links.
response_trans_res	Contains the response to the trans_res_1 or trans_res_2 schemas which are used to set up conferences, and to set up and manage Meeting Rooms, Entry Queues, SIP Factories and Profiles.
response_trans_res_list	Contains the response to the trans_res_list schema which is used to retrieve a list of Meeting Room, Entry Queue, SIP Factory and Profile summaries.
response_trans_rsrc_report	Contains the response to the trans_rsrc_report schema, which is used to retrieve a resource report for an RMX.
response_trans_rtm_isdn_span	Contains the response to the trans_rtm_isdn_span schema which is used to manage an ISDN/PSTN span.
response_trans_rtm_isdn_span_list	Contains the response to the trans_rtm_isdn_span_list which is used to retrieve details of ISDN/PSTN spans.
response_trans_snmp	Contains the response to the trans_snmp schema, which is used to manage the SNMP (Simple Network Management Protocol) configuration.
response_trans_tcp_dump	Contains the response to the trans_tcp_dump schema, which is used to for the TCP dump Network Traffic Capture interface. (Applicable from version 7.2)
trans_active_alarms_list	Used to retrieve system alerts.
trans_audit_file_summary_list	Used to retrieve a list of auditor file summaries.
trans_av_msg_service	Used to manage a Conference and Entry Queue IVR Service.
trans_av_msg_service_list	Used to retrieve information about Conference and Entry Queue IVR Services.
trans_card	Used to manage a card.
trans_cards_list	Used to retrieve details of all the cards in the MCU.
trans_cdr_full	Used to retrieve the complete CDR information from the MCU.
trans_cdr_list	Used to retrieve a list of CDR summaries from the MCU.
trans_certificate	Used to send certificates to the RMX.
trans_certificate_list	Used for Server Certificate monitoring. (Applicable in version 7.5.0.J and from version 7.6)

Schema	Description
trans_certificate_request	Used to create certificate requests.
trans_cfg	Used to manage system configuration flags.
trans_conf_1	The trans_conf_1 and trans_conf_2 schemas are used to manage conferences.
trans_conf_2	The trans_conf_1 and trans_conf_2 schemas are used to manage conferences.
trans_conf_list	Used to retrieve a list of conference summaries.
trans_conferences_rsrc	This schema is used for retrieving conferences resources per conference to be applied for the DMA process. (Applicable from version 7.6.1)
trans_connections_list	Used to retrieve connection information about all RMX users who are currently connected to the MCU.
trans_ethernet_settings	Used to manage the LAN ports of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
trans_ethernet_settings_list	Used to retrieve details of all LAN ports of the RMX 4000 and the RMX 1500/2000 when an RTM LAN card is installed. (Applicable from version 5.0)
trans_faults_list	Used to retrieve a full faults list.
trans_faults_list_short	Used to retrieve an abbreviated faults list, that is, a faults list without the asserts.
trans_hot_backup	Used to retrieve the hot backup configuration information and enables you to update the hot backup configuration. (Applicable from version 7.2)
trans_ip_service	Used to manage an IP and Management Network Service.
trans_ip_service_list	Used to retrieve details of IP and Management Network Services.
trans_isdn_phone	Used to manage ISDN/PSTN Network Service phone number ranges.
trans_isdn_service	Used to manage an ISDN/PSTN Network Service.
trans_isdn_service_list	Used to retrieve details of ISDN/PSTN Network Services.
trans_log_file_list	Used to retrieve a list of log file summaries.
trans_logger	Used to manage the Logger Configuration utility. (Applicable from version 7.6)
trans_mcu	Used to log in and out of the MCU, to retrieve information from the MCU, and to perform configuration and file operations on the MCU.
trans_oper_list	Used to retrieve information about all defined RMX users.
trans_operator	Used to manage an RMX user.
trans_party	Used to retrieve information about a participant in a conference.
trans_recording_links_list	Used to manage recording links.

Schema	Description
trans_res_1	The trans_res_1 and trans_res_2 schemas are used to set up conferences, and to set up and manage Meeting Rooms, Entry Queues, SIP Factories and Profiles.
trans_res_2	The trans_res_1 and trans_res_2 schemas are used to set up conferences, and to set up and manage Meeting Rooms, Entry Queues, SIP Factories and Profiles.
trans_res_list	Used to retrieve a list of Meeting Room, Entry Queue, SIP Factory and Profile summaries.
trans_rsrc_report	Used to retrieve a resource report for an RMX.
trans_rtm_isdn_span	Used to manage an ISDN/PSTN span.
trans_rtm_isdn_span_list	Used to retrieve details of ISDN/PSTN spans.
trans_snmp	Used to manage the SNMP (Simple Network Management Protocol) configuration.
trans_tcp_dump	Contains the requests for the TCP dump Network Traffic Capture interface. (Applicable from version 7.2)

Note: In addition to the schemas listed above, the RMX XML API developer's kit contains the following schemas that are for internal use only, but are included in the XML API developer's kit because they are referenced by other schemas:

- obj_common_full_list
- obj_conf_full_list
- obj_gateway
- obj_junction
- obj_mcu_lan_configuration
- obj_mcu_memory_state
- obj_performance_monitoring
- obj_span

These schemas are located in the **Internal** folder.

Working with the RMX XML API

Communicating with the RMX XML API

The RMX XML API can be used with any environment that can post HTTP streams. You need to open an HTTP connection against each MCU with which you want to work.

The client application sends an XML string to the internal HTTP server in the MCU.

A module in the internal web site performs validation checks on the XML string.

If the XML string fails the validation, the MCU sends an error status to the client application via the internal web site.

If the XML string is OK, it is translated to C++ and sent to the MCU. The MCU then sends a response to the client application.

XML Requests and Responses

All XML API requests have an input parameter which contains an XML string. The XML string can be specified in various formats, for example, char*, BSTR or MSDOM. This input parameter will be referred to as the REQUEST_XML.

All XML API responses return an output parameter which contains an XML string in the same format as the input parameter. The output parameter will be referred as the RESPONSE_XML.

Example of the procedure for working with the RMX XML API from Internet Explorer using Java Script

1. Create an HTTP connection object, as follows:

```
var httpConnection = new ActiveXObject("Microsoft.XMLHTTP");
```

2. Open an HTTP connection, pointing it to the URL of the XTransactionSubmit.asp which is located in the MCU, as follows:

```
httpConnection.Open("POST", "MCU IP Address/XTransactionSubmit.  
asp", false);
```

3. Post the XML to the MCU, as follows:

```
httpConnection.Send(REQUEST_XML);
```

4. **httpConnection.responseText** will hold the XML_RESPONSE string.

The RMX XML API Internal XML Parser

The RMX XML API uses an internal XML parser. Like the Microsoft XML parser, this internal parser uses certain characters as control characters. For example, if you include the greater than (>) character in an XML element, the internal parser will interpret this character as an end of element symbol, and an error will occur. To avoid this problem you need to replace these special characters in the XML stream with the appropriate entity reference, as detailed in the table below:

Special Character	Entity Reference
&	&
<	<
>	>
'	'
"	"

When the RMX XML API internal parser encounters an entity reference in an XML stream, it converts the entity reference to the appropriate special character. Similarly, when the internal parser returns an XML stream, the stream will contain entity references instead of the equivalent special characters. You can then convert these entity references back to the appropriate special character.

Logging in to the MCU

You need to log in to the MCU for each socket you connect through, and cannot connect through a new socket using the old token obtained when logging in through a different socket. To connect through a different socket, you must log in again using XML.

The RMX XML API can currently only be used with port 80. The preferred port is now hard-coded, and cannot be changed in system.cfg.

The trans_mcu Schema

The first thing you have to do to before sending any transactions to the MCU is to log in to the MCU. This is done according to the **trans_mcu** schema shown below:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
elementFormDefault="qualified">
```

```
<xsd:include schemaLocation="common_trans.xsd"/>
<xsd:include schemaLocation="obj_mcu_lan_configuration.xsd"/>
<xsd:include schemaLocation="obj_mcu_time.xsd"/>
<xsd:include schemaLocation="obj_exchange_cfg.xsd"/>
<xsd:include schemaLocation="obj_resolutions_set.xsd"/>
<xsd:include schemaLocation="obj_collect_info.xsd"/>
<xsd:include schemaLocation="obj_active_directory.xsd"/>
```



```
<!-- In most transaction schemas, details of the choices are to be found at the
beginning of the schema. These are the ACTIONS (functions) that can be performed. -
->

<xsd:element name="LOGIN" type="LoginRequestContent"/>

<!-- The LoginRequestContent type is defined in common_trans.xsd and is explained
later.-->

<xsd:element name="LOGOUT" type="LogoutContent"/>
<xsd:element name="GET_STATE"/>
<xsd:element name="RMX_GET_STATE_EX" type="RmxGetStateExContent"/>
<xsd:element name="GET_MEMORY_STATE"/>
<xsd:element name="GET_LAN_CONFIGURATION"/>
<xsd:element name="GET_TIME"/>
<xsd:element name="GET_CFS"/>
<xsd:element name="RESET"/>
<xsd:element name="GET_RECORDING_JUNCTION_LIST"/>
<xsd:element name="FILE_UPDATED_STRING" type="xsd:string"/>
<xsd:element name="PATH" type="xsd:string"/>
<xsd:element name="NEW_NAME" type="xsd:string"/>
<xsd:element name="GET_DIRECTORY" type="DirectoryPath"/>
<xsd:element name="GET_DIRECTORY_RECURSIVE" type="DirectoryPath"/>
<xsd:element name="GET_VIRTUAL_DIRECTORY" type="DirectoryPath"/>
<xsd:element name="GET_VIRTUAL_DIRECTORY_RECURSIVE" type="DirectoryPath"/>
<xsd:element name="REMOVE_DIRECTORY" type="DirectoryPath"/>
<xsd:element name="REMOVE_DIRECTORY_CONTENT" type="DirectoryPath"/>
<xsd:element name="BEGIN_RECEIVING_VERSION"/>
<xsd:element name="FINISHED_TRANSFER_VERSION"/>
<xsd:element name="UPDATE_KEY_CODE" type="KeyCodeContent"/>
<xsd:element name="FLUSH"/>
<xsd:element name="STOP_ALL_MEDIA_RECORDING"/>
<xsd:element name="RESTORE_TYPE" type="RestoreType"/>
<xsd:element name="COLLECT_INFO" type="CollectInfoContent"/>
<xsd:element name="GET_COLLECT_INFO_SETTINGS"/>
<xsd:element name="ABORT_COLLECT_INFO"/>
<xsd:element name="GET_INSTALLATION_STATUS"/>
<xsd:element name="TURN_SSH" type="TurnSSHContent"/>
<xsd:element name="GET_PORT_CONFIGURATION"/>
<xsd:element name="SET_PORT_CONFIGURATION" type="PortConfigurationIndex"/>
<xsd:element name="GET_ENHANCED_PORT_CONFIGURATION"/>
<xsd:element name="GET_CHECK_ENHANCED_PORT_CONFIGURATION"
type="EnhancedPortNumConfiguration"/>
<xsd:element name="SET_ENHANCED_PORT_CONFIGURATION"
type="EnhancedPortNumConfiguration"/>
<xsd:element name="AUDIO_NUM_PORTS_CONFIG" type="xsd:integer"/>
<xsd:element name="CIF_NUM_PORTS_CONFIG" type="xsd:integer"/>
<xsd:element name="SD_NUM_PORTS_CONFIG" type="xsd:integer"/>
```

```

<xsd:element name="HD720_NUM_PORTS_CONFIG" type="xsd:integer"/>
<xsd:element name="HD1080_NUM_PORTS_CONFIG" type="xsd:integer"/>
<xsd:element name="INSTALL_PREVIOUS_VERSION"
type="InstallPreviousVersionContent"/>
<xsd:element name="VERSION_TYPE" type="VersionType"/>
<xsd:element name="GET_ALLOCATION_MODE"/>
<xsd:element name="SET_ALLOCATION_MODE" type="SelectedAllocationModeContent"/>
<xsd:element name="SELECTED_ALLOCATION_MODE" type="AllocationModeType"/>
<xsd:element name="BACKUP_CONFIG_START"/>
<xsd:element name="BACKUP_CONFIG_FINISH"/>
<xsd:element name="RESTORE_CONFIG_START"/>
<xsd:element name="RESTORE_CONFIG_FINISH" type="RestoreCfgFinish"/>
<xsd:element name="REASON" type="LogoutReasonType" default="normal"/>
<xsd:element name="SET_PING" type="SetPingContent"/>
<xsd:element name="GET_PING" type="GetPingContent"/>
<xsd:element name="GET_MCU_EXCHANGE_CONFIG_PARAMS"/>
<xsd:element name="SET_MCU_EXCHANGE_CONFIG_PARAMS"
type="SetMcuExchangeConfigParams"/>
<xsd:element name="GET_LAST_SET_MCU_EXCHANGE_CONFIG_INDICATION"/>
<xsd:element name="GET_RESOLUTIONS_SET"/>
<xsd:element name="GET_ACTIVE_DIRECTORY_CONFIGURATION"/>
<xsd:element name="SET_ACTIVE_DIRECTORY_CONFIGURATION"
type="SetActiveDirectoryConfiguration"/>
<xsd:element name="GET_AD_SERVER_AVAILABILITY_STATUS"/>
<xsd:element name="GET_LAST_UPDATE_KEY_CODE_INDICATION"/

<xsd:complexType name="RestoreCfgFinish">
    <xsd:sequence>
        <xsd:element name="RESTORE_CONFIG_FILE" type="xsd:string"/>
        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="VersionType">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="fallback"/>
        <xsd:enumeration value="factory"/>
    </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="InstallPreviousVersionContent">
    <xsd:sequence>
        <xsd:element ref="VERSION_TYPE"/>

```

```

        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
            namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="RestoreType">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="standard"/>
        <xsd:enumeration value="extensive"/>
    </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="KeyCodeContent">
    <xsd:sequence>
        <xsd:element name="KEY_CODE" type="xsd:string"/>
        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
            namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="CollectInfoContent">
    <xsd:sequence>
        <xsd:element ref="START_TIME"/>
        <xsd:element ref="END_TIME"/>
        <xsd:element ref="COLLECT_INFO_LIST"/>
        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
            namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="DirectoryPath">
    <xsd:sequence>
        <xsd:element ref="PATH"/>
        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
            namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="TurnSSHContent">
    <xsd:sequence>
        <xsd:element ref="ON"/>
        <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
            namespace="##other"/>
    </xsd:sequence>
</xsd:complexType>

```

```

<!-- The root elements in the transaction schemas have the same name as the schema
name. -->
<xsd:element name="TRANS_MCU">
<xsd:complexType>
    <xsd:sequence>
        <!-- The first element in all transaction schemas is the TRANS_COMMON_PARAMS
        element. This complex element is defined in common_trans.xsd and is explained
        later.-->
        <xsd:element ref="TRANS_COMMON_PARAMS"/>
        <!-- In all transaction schemas a choice of the ACTIONS group or the ACTION
        element comes next. The ACTION element contains the ACTIONS group which
        identifies which operation you want to perform. In this case the choices are
        LOGIN, LOGOUT, GET_STATE and so on, as defined further down in the schema. -->
        <xsd:choice>
            <xsd:group ref="ACTIONS"/>
            <xsd:element ref="ACTION"/>
        </xsd:choice>
        <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
</xsd:element>

<xsd:element name="SET_LAN_CONFIGURATION">
<xsd:complexType>
    <xsd:sequence>
        <xsd:element ref="MCU_LAN_CONFIGURATION"/>
        <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
</xsd:element>

<xsd:element name="SET_TIME">
<xsd:complexType>
    <xsd:sequence>
        <xsd:element ref="MCU_TIME"/>
        <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
</xsd:element>

```

```
<xsd:element name="SHIFT_RESERVATIONS_TIME">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="SHIFT_RESERVATIONS"/>
      <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
        namespace="##other"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

```
<xsd:element name="FILE_UPDATED">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="FILE_UPDATED_STRING"/>
      <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

```
<xsd:element name="CREATE_DIRECTORY">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="PATH"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

```
<xsd:element name="RENAME">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="PATH"/>
      <xsd:element ref="NEW_NAME"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

```

<xsd:element name="SET_RESTORE_TYPE">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="RESTORE_TYPE"/>
      <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>

<xsd:complexType name="PortConfigurationIndex">
  <xsd:sequence>
    <xsd:element ref="SELECTED_ID"/>
    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="EnhancedPortNumConfiguration">
  <xsd:sequence>
    <xsd:element ref="AUDIO_NUM_PORTS_CONFIG"/>
    <xsd:element ref="CIF_NUM_PORTS_CONFIG"/>
    <xsd:element ref="SD_NUM_PORTS_CONFIG"/>
    <xsd:element ref="HD720_NUM_PORTS_CONFIG"/>
    <xsd:element ref="HD1080_NUM_PORTS_CONFIG"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="##other"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="SelectedAllocationModeContent">
  <xsd:sequence>
    <xsd:element ref="SELECTED_ALLOCATION_MODE"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="##other"/>
  </xsd:sequence>
</xsd:complexType>

```

```
<xsd:simpleType name="LogoutReasonType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="normal"/>
    <xsd:enumeration value="session_expired"/>
  </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="LogoutContent">
  <xsd:sequence>
    <xsd:element ref="REASON"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="SetPingContent">
  <xsd:sequence>
    <xsd:element ref="PING"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="GetPingContent">
  <xsd:sequence>
    <xsd:element ref="PING_ID"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="SetMcuExchangeConfigParams">
  <xsd:sequence>
    <xsd:element ref="MCU_EXCHANGE_CONFIG_PARAMS"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>
```

```

<xsd:complexType name="RmxGetStateExContent">
  <xsd:sequence>
    <xsd:element ref="CLIENT_IP" minOccurs="0"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>

<xsd:element name="SET_RESOLUTIONS_SET">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="SET_RESOLUTIONS_PARAMS"/>
      <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
        namespace="###other"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>

<xsd:complexType name="SetActiveDirectoryConfiguration">
  <xsd:sequence>
    <xsd:element ref="ACTIVE_DIRECTORY_CONFIG_PARAMS"/>
    <xsd:any processContents="skip" minOccurs="0" maxOccurs="unbounded"
      namespace="###other"/>
  </xsd:sequence>
</xsd:complexType>

<!-- The list of ACTIONS to choose from. -->
<xsd:group name="ACTIONS">
  <xsd:choice>
    <xsd:element ref="LOGIN"/>
    <xsd:element ref="LOGOUT"/>
    <xsd:element ref="GET_STATE"/>
    <xsd:element ref="GET_MEMORY_STATE"/> <!--not supported-->
    <xsd:element ref="RESET"/>
    <xsd:element ref="GET_LAN_CONFIGURATION"/> <!--not supported-->
    <xsd:element ref="SET_LAN_CONFIGURATION"/> <!--not supported-->
    <xsd:element ref="GET_TIME"/>
    <xsd:element ref="SET_TIME"/>
    <xsd:element ref="GET_DIRECTORY"/>
    <xsd:element ref="GET_DIRECTORY_RECURSIVE"/> <!--not supported-->
    <xsd:element ref="GET_VIRTUAL_DIRECTORY"/>
    <xsd:element ref="GET_VIRTUAL_DIRECTORY_RECURSIVE"/>
    <xsd:element ref="FILE_UPDATED"/> <!--not supported-->
    <xsd:element ref="CREATE_DIRECTORY"/>
  </xsd:choice>
</xsd:group>

```



```
<xsd:element ref="RENAME"/>
<xsd:element ref="REMOVE_DIRECTORY"/>
<xsd:element ref="BEGIN_RECEIVING_VERSION"/>
<xsd:element ref="FINISHED_TRANSFER_VERSION"/>
<xsd:element ref="UPDATE_KEY_CODE"/>
<xsd:element ref="FLUSH"/>
<xsd:element ref="GET_CFS"/>
<xsd:element ref="STOP_ALL_MEDIA_RECORDING"/>
<xsd:element ref="GET_RECORDING_JUNCTION_LIST"/>
<xsd:element ref="SET_RESTORE_TYPE"/>
<xsd:element ref="COLLECT_INFO"/>
<xsd:element ref="GET_COLLECT_INFO_SETTINGS"/>
<xsd:element ref="ABORT_COLLECT_INFO"/>
<xsd:element ref="GET_INSTALLATION_STATUS"/>
<xsd:element ref="TURN_SSH"/>
<xsd:element ref="REMOVE_DIRECTORY_CONTENT"/>
<xsd:element ref="GET_PORT_CONFIGURATION"/>
<xsd:element ref="SET_PORT_CONFIGURATION"/>
<xsd:element ref="GET_ENHANCED_PORT_CONFIGURATION"/>
<xsd:element ref="GET_CHECK_ENHANCED_PORT_CONFIGURATION"/>
<xsd:element ref="SET_ENHANCED_PORT_CONFIGURATION"/>
<xsd:element ref="INSTALL_PREVIOUS_VERSION"/>
<xsd:element ref="GET_ALLOCATION_MODE"/>
<xsd:element ref="SET_ALLOCATION_MODE"/>
<xsd:element ref="BACKUP_CONFIG_START"/>
<xsd:element ref="BACKUP_CONFIG_FINISH"/>
<xsd:element ref="RESTORE_CONFIG_START"/>
<xsd:element ref="RESTORE_CONFIG_FINISH"/>
<xsd:element ref="SET_PING"/>
<xsd:element ref="GET_PING"/>
<xsd:element ref="RMX_GET_STATE_EX"/>
<xsd:element ref="GET_MCU_EXCHANGE_CONFIG_PARAMS"/>
<xsd:element ref="SET_MCU_EXCHANGE_CONFIG_PARAMS"/>
<xsd:element ref="GET_LAST_SET_MCU_EXCHANGE_CONFIG_INDICATION"/>
<xsd:element ref="GET_RESOLUTIONS_SET"/>
<xsd:element ref="SET_RESOLUTIONS_SET"/>
<xsd:element ref="GET_ACTIVE_DIRECTORY_CONFIGURATION"/>
<xsd:element ref="SET_ACTIVE_DIRECTORY_CONFIGURATION"/>
```

```

        <xsd:element ref="GET_AD_SERVER_AVAILABILITY_STATUS"/>
        <xsd:element ref="GET_LAST_UPDATE_KEY_CODE_INDICATION"/>
        <xsd:element ref="SHIFT_RESERVATIONS_TIME"/>
    </xsd:choice>
</xsd:group>

```

```

<xsd:element name="ACTION">
    <xsd:complexType>
        <xsd:sequence>
            <xsd:group ref="ACTIONS"/>
        </xsd:sequence>
    </xsd:complexType>
</xsd:element>

```

The LoginRequestContent type and the MCU_IP and LISTEN_PORT elements are defined in the common_trans schema.

```

<xsd:complexType name="LoginRequestContent">
    <xsd:sequence>
        <!-- The MCU IP & port number see below. -->
        <xsd:element ref="MCU_IP"/>
        <!-- The user name and password to log in to the MCU. -->
        <xsd:element ref="USER_NAME"/>
        <xsd:element ref="PASSWORD"/>
        <xsd:element ref="STATION_NAME" minOccurs="0"/>
        <xsd:element ref="COMPRESSION" minOccurs="0"/>
        <xsd:element ref="CONFERENCE_RECORDER" minOccurs="0"/> <!--not supported-->
        <xsd:element ref="NEW_PASSWORD" minOccurs="0"/> <!--not supported-->
        <xsd:any namespace="##other" processContents="skip" minOccurs="0"
            maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>

<xsd:element name="MCU_IP" type="McuContent"/>

<xsd:complexType name="McuContent">
    <xsd:sequence>
        <xsd:element ref="IP"/> <!-- The IP of the MCU. -->
        <xsd:element ref="LISTEN_PORT" minOccurs="0"/> <!--relevant only
            when connecting-->
        <xsd:element ref="HOST_NAME" minOccurs="0"/>
        <xsd:any namespace="##other" processContents="skip" minOccurs="0"
            maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>

```

```

<xsd:element name="LISTEN_PORT" type="xsd:integer"/>

<!-- The TRANS_COMMON_PARAMS element.
As stated earlier, each trans_xxx schema starts with the TRANS_COMMON_PARAMS
element, which is defined in the common_trans schema.
Below is the definition of TRANS_COMMON_PARAMS. -->

<xsd:element name="TRANS_COMMON_PARAMS" type="TransCommonParamsContent"/>
.
<xsd:complexType name="TransCommonParamsContent">
  <xsd:sequence>
    <!-- After logging in, you will get two tokens that you will have to send in
    each transaction. However, in the login transaction itself, these tokens
    have no meaning. -->

    <!-- The MCU_TOKEN is the identifier of the MCU. -->
    <xsd:element ref="MCU_TOKEN"/>

    <!-- The MCU_USER_TOKEN identifies the logger to the MCU for security
    purposes. -->
    <xsd:element ref="MCU_USER_TOKEN"/>

    <!-- The synchronization method. -->
    <xsd:group ref="SYNC_CHOICE" minOccurs="0"/>
    <xsd:element ref="MESSAGE_ID" minOccurs="0"/>

    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
    maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

<!-- The SYNC_CHOICE element below is optional. However, if your client works
asynchronously, and you want to use tokens or pointers to help identify
transaction responses, then you should specify the ASYNC value for the SYNC_CHOICE
element. Then you can use the YOUR_TOKEN1 or YOUR_TOKEN2 elements that are
contained in the ASYNC element to save a token, or pointer, or any 32 bit data. --
>

<xsd:group name="SYNC_CHOICE">
  <xsd:choice>
    <xsd:element ref="ASYNC"/>
    <xsd:element ref="SYNC"/>
  </xsd:choice>
</xsd:group>

```

```
<!-- Below is the full definition of the ASYNC element. -->
<xsd:element name="ASYNC" type="AsyncContent"/>
<xsd:complexType name="AsyncContent">
  <xsd:sequence>
    <!-- The first three elements, ASYNC_METHOD, URL and PORT_NUMBER are
    obsolete. -->
    <xsd:element ref="ASYNC_METHOD"/>
    <xsd:element ref="URL" minOccurs="0"/>
    <xsd:element ref="PORT_NUMBER" minOccurs="0"/>
    <!-- In YOUR_TOKEN1 save your token or pointer or any 32 bit data that
    will return to you. -->
    <xsd:element ref="YOUR_TOKEN1" minOccurs="0"/>
    <!-- In YOUR_TOKEN2 save your token or pointer or any 32 bit data that
    will return to <xsd:element ref="YOUR_TOKEN2" minOccurs="0"/>
    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
    maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

An XML Example

The following example shows the login XML sent to the MCU, and the corresponding response XML.

```
<TRANS_MCU><!-- The root is the transaction name. -->
  <TRANS_COMMON_PARAMS>
    <!-- In the login transaction the next two parameters have no meaning. Just
    send 0. -->
    <MCU_TOKEN>0</MCU_TOKEN>
    <MCU_USER_TOKEN>0</MCU_USER_TOKEN>
    <MESSAGE_ID>1</MESSAGE_ID>
  </TRANS_COMMON_PARAMS>
  <!-- The next element is the action (Login), and below it are the action's
  parameters, in this case, the Login parameters. -->
  <ACTION>
    <LOGIN>
      <!-- The next parameters are the MCU IP and the port number. -->
      <MCU_IP>
        <IP>172.22.189.154</IP>
        <LISTEN_PORT>80</LISTEN_PORT>
        <HOST_NAME/>
      </MCU_IP>
      <!-- The user and password strings. -->
      <USER_NAME>POLYCOM</USER_NAME>
      <PASSWORD>POLYCOM</PASSWORD>
      <STATION_NAME>EMA.F3-JUDITHS</STATION_NAME>
```

```
<COMPRESSION>true</COMPRESSION>
</LOGIN>
</ACTION>
</TRANS_MCU>
```

The response will be according to the **response_trans_mcu** schema:

```
<RESPONSE_TRANS_MCU>
<!-- The status of the action, STATUS_OK (success). -->
  <RETURN_STATUS>
    <ID>0</ID>
    <DESCRIPTION>STATUS_OK</DESCRIPTION>
    <YOUR_TOKEN1>0</YOUR_TOKEN1>
    <YOUR_TOKEN2>0</YOUR_TOKEN2>
    <MESSAGE_ID>1</MESSAGE_ID>
    <DESCRIPTION_EX/>
  </RETURN_STATUS>
  <ACTION>
    <!-- The sent action -->
    <LOGIN>
      <!-- The two tokens that you should keep and send with all further
      transactions. -->
      <MCU_TOKEN>537</MCU_TOKEN>
      <MCU_USER_TOKEN>537</MCU_USER_TOKEN>
      <VERSION_LIST><!-- The version numbers.-->
        <MCU_VERSION>
          <MAIN>1</MAIN>
          <MAJOR>1</MAJOR>
          <MINOR>0</MINOR>
          <INTERNAL>70</INTERNAL>
          <PRIVATE_DESCRIPTION>vasily_2007-01-25_14-
          36</PRIVATE_DESCRIPTION>
        </MCU_VERSION>
        <MCMS_VERSION>
          <MAIN>0</MAIN>
          <MAJOR>0</MAJOR>
          <MINOR>0</MINOR>
          <INTERNAL>0</INTERNAL>
          <PRIVATE_DESCRIPTION/>
        </MCMS_VERSION>
      </VERSION_LIST>
      <AUTHORIZATION_GROUP>administrator</AUTHORIZATION_GROUP>
      <API_NUMBER>2000</API_NUMBER>
      <PRODUCT_TYPE>Rmx_2000</PRODUCT_TYPE>
```

```

        <HTTP_PORT>80</HTTP_PORT>
    </LOGIN>
</ACTION>
</RESPONSE_TRANS_MCU>

```

Keeping the Connection with the MCU Alive

If any XML API call is not performed within an interval of two minutes, the MCU will disconnect the client, and your token numbers (MCU_TOKEN and MCU_USER_TOKEN) will no longer be valid.

If your application interacts frequently with the XML API, it is highly recommended to keep the connection alive, and use the tokens that you receive from the initial login request for all transactions. Do not log in and log out for each request, as this can cause problems with the RMX XML API and the RMX client.

To keep the connection alive, make your application send an XML page every 30 seconds (at least). For example, you can send the following XML transaction to get the MCU state:

```

<!-- The root is the transaction name. -->
<TRANS_MCU>
    <TRANS_COMMON_PARAMS>
        <MCU_TOKEN>26</MCU_TOKEN>
        <MCU_USER_TOKEN>26</MCU_USER_TOKEN>
        <MESSAGE_ID>147</MESSAGE_ID>
    </TRANS_COMMON_PARAMS>
    <ACTION>
        <GET_STATE/>
    </ACTION>
</TRANS_MCU>


```

Working with the Response and Transaction Schemas

The response and transaction schemas generally contain an element named **ACTION**. This element contains a group named **ACTIONS**, which contains a choice of action elements. Each action element identifies an action that can be requested using the schema, or to which a response is being returned by the schema.


We recommend that when using the response and transaction schemas, you use the **ACTION** element and the **ACTIONS** group, although for compatibility with the XAP you can use the **ACTION** group as in the past.

For example, in the **trans_res_1** schema, the **ACTION** element, contains the **ACTIONS** group, which contains the **START_REPEATED** (*not supported*), **START**, **UPDATE**, **LOGIN_START** (*not supported*), **SET_DEFAULT_EQ** and **CANCEL_DEFAULT_EQ** elements, as shown below:



```
<xsd:element name="ACTION">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:group ref="ACTIONS"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
<xsd:group name="ACTIONS">
  <xsd:choice>
    <xsd:element ref="START_REPEATED"/>    <!--not supported-->
    <xsd:element ref="START"/>
    <xsd:element ref="UPDATE"/>
    <xsd:element ref="LOGIN_START"/>    <!--not supported-->
    <xsd:element ref="SET_DEFAULT_EQ"/>
    <xsd:element ref="CANCEL_DEFAULT_EQ"/>
  </xsd:choice>
</xsd:group>
```

The **TRANS_RES_1** element contains a choice of the **ACTIONS** group and the **ACTION** element, as shown below:




```
<xsd:element name="TRANS_RES_1">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="TRANS_COMMON_PARAMS"/>
      <xsd:choice>
        <xsd:group ref="ACTIONS"/>
        <xsd:element ref="ACTION"/>
      </xsd:choice>
      <xsd:any namespace="##other" processContents="skip" minOccurs="0"
        maxOccurs="unbounded"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

Audio Muting a Participant - An XML Example

This example shows the XML that must be sent in order to audio mute a party according to the **trans_conf_2** schema, and the response that will be received.

```
<TRANS_CONF_2>
  <TRANS_COMMON_PARAMS>
    <MCU_TOKEN>1005</MCU_TOKEN>
    <MCU_USER_TOKEN>1005</MCU_USER_TOKEN>
    <ASYNCR>
      <YOUR_TOKEN1>0</YOUR_TOKEN1>
      <YOUR_TOKEN2>0</YOUR_TOKEN2>
    </ASYNCR>
    <MESSAGE_ID>85</MESSAGE_ID>
  </TRANS_COMMON_PARAMS>
  <ACTION>
    <SET_AUDIO_VIDEO_MUTE>
      <ID>2</ID>
      <AUDIO_MUTE>true</AUDIO_MUTE>
      <VIDEO_MUTE>false</VIDEO_MUTE>
      <PARTY_ID>0</PARTY_ID>
    </SET_AUDIO_VIDEO_MUTE>
  </ACTION>
</TRANS_CONF_2>
```


The response will be as follows, according to the **response_trans_conf** schema:

```
<RESPONSE_TRANS_CONF>
  <RETURN_STATUS>
    <ID>1</ID>
    <DESCRIPTION>IN_PROGRESS</DESCRIPTION>
    <YOUR_TOKEN1>0</YOUR_TOKEN1>
    <YOUR_TOKEN2>0</YOUR_TOKEN2>
    <MESSAGE_ID>85</MESSAGE_ID>
    <DESCRIPTION_EX/>
  </RETURN_STATUS>
  <ACTION>
    <SET_AUDIO_VIDEO_MUTE/>
  </ACTION>
</RESPONSE_TRANS_CONF>
```

Transaction Processing

The client is responsible for managing transactions. The MCU itself returns responses immediately. The RMX XML API provides two tokens which can be used to identify the transaction response. These tokens are returned in the **YOUR_TOKEN1** and **YOUR_TOKEN2** elements which are contained in the **ASYNC** element in the **SYNC_CHOICE** group in the **TRANS_COMMON_PARAMS** element in the **common_trans** schema.

The **SYNC_CHOICE** group is optional, and only needs to be specified if you want to use the contents of the **YOUR_TOKEN1** and **YOUR_TOKEN2** elements, and in this case should be specified with the **ASYNC** value. The **SYNC** value is obsolete.




```

<xsd:element name="TRANS_COMMON_PARAMS" type="TransCommonParamsContent"/>
<xsd:complexType name="TransCommonParamsContent">
  <xsd:sequence>
    <xsd:element ref="MCU_TOKEN"/>
    <xsd:element ref="MCU_USER_TOKEN"/>
    <xsd:group ref="SYNC_CHOICE" minOccurs="0"/>
    <xsd:element ref="MESSAGE_ID" minOccurs="0"/>
    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```


If you wish to use user tokens or pointers to help identify transaction responses, you should specify the **ASync** value for the **SYNC_CHOICE** group. Then when sending a transaction, you can use **YOUR_TOKEN1** or **YOUR_TOKEN2** to save a token or pointer or any 32 bit data.



```

<xsd:group name="SYNC_CHOICE">
  <xsd:choice>
    <xsd:element ref="ASync"/>
    <xsd:element ref="SYNC"/>
  </xsd:choice>
</xsd:group>

```



```

<xsd:complexType name="AsyncContent">
  <!-- The ASYNC_METHOD, URL and PORT_NUMBER elements are obsolete. The YOUR_TOKEN1
  and YOUR_TOKEN2 elements can be used to save tokens, pointers or any 32 bit data
  to be used to identify transaction responses when the client application is
  working in asynchronous mode. -->
  <xsd:sequence>
    <xsd:element ref="ASYNC_METHOD" minOccurs="0"/>
    <xsd:element ref="URL" minOccurs="0"/>
    <xsd:element ref="PORT_NUMBER" minOccurs="0"/>
    <xsd:element ref="YOUR_TOKEN1" minOccurs="0"/>
    <xsd:element ref="YOUR_TOKEN2" minOccurs="0"/>
    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
    maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```

Polling for Data

The XML API cannot push requested data when data is changed. Therefore when you want to monitor objects like conferences you have to poll for them. It is recommended to poll for data every 30 seconds using the GET_STATE transaction from the **trans_mcu** schema.

The XML API provides a mechanism to make the polling more efficient. When you query for an object, the RESPONSE_XML contains an object token, OBJ_TOKEN. If you send this token in your next request, then the RESPONSE_XML will include any members in the object that were changed since the previous call, and a new object token. If no changes were made, you will get the same token and no data. The RESPONSE_XML also contains a flag indicating if there any changes were made.

For example, if a participant was added to a conference after you made a get request, then in the next request, provided that you send the correct object token, you will only get the data of the new participant. If participants were removed, you will get a list of the deleted participants.

For any get request, if you want to get the full data, send **-1** in the object token.

The following is an XML example for retrieving the Meeting Room list:

Note: The Meeting Room list contains Meeting Room, Entry Queue and SIP Factory summary information.

The initial REQUEST_XML

```
<TRANS_RES_LIST>
  <TRANS_COMMON_PARAMS>
    <MCU_TOKEN>3</MCU_TOKEN>
    <MCU_USER_TOKEN>3</MCU_USER_TOKEN>
    <MESSAGE_ID>143</MESSAGE_ID>
  </TRANS_COMMON_PARAMS>
  <ACTION>
    <GET_MEETING_ROOM_LIST>
      <OBJ_TOKEN>-1</OBJ_TOKEN>
      <!-- The object token is -1, in order to get the full data. -->
    </GET_MEETING_ROOM_LIST>
  </ACTION>
</TRANS_RES_LIST>
```

The RESPONSE_XML (one Meeting Room in the list)

```
<RESPONSE_TRANS_RES_LIST>
  <RETURN_STATUS>
    <ID>0</ID>
    <DESCRIPTION>STATUS_OK</DESCRIPTION>
    <YOUR_TOKEN1>0</YOUR_TOKEN1>
    <YOUR_TOKEN2>0</YOUR_TOKEN2>
    <MESSAGE_ID>143</MESSAGE_ID>
    <DESCRIPTION_EX/>
  </RETURN_STATUS>
  <ACTION>
    <GET_MEETING_ROOM_LIST>
      <MEETING_ROOM_SUMMARY_LS>
        <OBJ_TOKEN>12</OBJ_TOKEN>
        <!-- The returned object token is 1. This will be used in the next get. -->
        <CHANGED>true</CHANGED>
        <DELETED_RES_LIST/>
        <DEFAULT_EQ_NAME/>
        <MEETING_ROOM_SUMMARY>
          <NAME>Maple_Room</NAME>
          <ID>0</ID>
          <RES_CHANGE>new</RES_CHANGE>
          <DURATION>
            <HOUR>2</HOUR>
            <MINUTE>0</MINUTE>
            <SECOND>0</SECOND>
          </DURATION>
        </MEETING_ROOM_SUMMARY>
      </MEETING_ROOM_SUMMARY_LS>
    </GET_MEETING_ROOM_LIST>
  </ACTION>
</RESPONSE_TRANS_RES_LIST>
```

```

    <MEET_ME_PHONE />
    <MR_STATE>passive</MR_STATE>
    <ENTRY_QUEUE>false</ENTRY_QUEUE>
    <ENTRY_PASSWORD>0512</ENTRY_PASSWORD>
    <PASSWORD>2968</PASSWORD>
    <NUMERIC_ID>1000</NUMERIC_ID>
    <NUM_PARTIES>0</NUM_PARTIES>
    <NUM_UNDEFINED_PARTIES>0</NUM_UNDEFINED_PARTIES>
    <DIAL_IN_H323_SRV_PREFIX_LIST>
      <DIAL_IN_H323_SRV_PREFIX>
        <NAME>Default IP Service</NAME>
        <PREFIX>9431</PREFIX>
      </DIAL_IN_H323_SRV_PREFIX>
    </DIAL_IN_H323_SRV_PREFIX_LIST>
    <ENCRYPTION>false</ENCRYPTION>
    <SIP_FACTORY>false</SIP_FACTORY>
    <AD_HOC_PROFILE_ID>1</AD_HOC_PROFILE_ID>
    <DISPLAY_NAME>Maple_Room</DISPLAY_NAME>
    <IS_TELEPRESENCE_MODE>false</IS_TELEPRESENCE_MODE>
  </MEETING_ROOM_SUMMARY>
</MEETING_ROOM_SUMMARY_LS>
</GET_MEETING_ROOM_LIST >
</ACTION>
</RESPONSE_TRANS_RES_LIST>

```

The next REQUEST_XML

```

<TRANS_RES_LIST>
  <TRANS_COMMON_PARAMS>
    <MCU_TOKEN>3</MCU_TOKEN>
    <MCU_USER_TOKEN>3</MCU_USER_TOKEN>
    <MESSAGE_ID>177</MESSAGE_ID>
  </TRANS_COMMON_PARAMS>
  <ACTION>
    <GET_MEETING_ROOM_LIST>
      <OBJ_TOKEN>12</OBJ_TOKEN>
      <!-- The object token is 1 as returned in the previous received object, in order
      to get differential data. -->
    </GET_MEETING_ROOM_LIST>
  </ACTION>
</TRANS_RES_LIST>

```

If no changes happened in the list, the RESPONSE_XML will be:

```

<RESPONSE_TRANS_RES_LIST>
  <RETURN_STATUS>

```

```

<ID>0</ID>
<DESCRIPTION>STATUS_OK</DESCRIPTION>
<YOUR_TOKEN1>0</YOUR_TOKEN1>
<YOUR_TOKEN2>0</YOUR_TOKEN2>
<MESSAGE_ID>177</MESSAGE_ID>
<DESCRIPTION_EX/>
</RETURN_STATUS>
<ACTION>
  <GET_MEETING_ROOM_LIST>
    <MEETING_ROOM_SUMMARY_LS>
      <OBJ_TOKEN>12</OBJ_TOKEN>
      <!-- The returned object token is the same as in the previous
      get request, since no changes were made. -->
      <CHANGED>>false</CHANGED>
    </MEETING_ROOM_SUMMARY_LS>
  </GET_MEETING_ROOM_LIST>
</ACTION>
</RESPONSE_TRANS_RES_LIST>

```

Retrieving Channel Information for IP Participants

Detailed channel information for IP participants is returned in the **IP_MONITOR_CHANNELS** element, which is contained in the **ONGOING_PARTY** element in the **obj_ongoing_party** schema. Since this element contains a large amount of information, its contents are only retrieved in response to the **trans_party GET** transaction, and not in response to the **trans_conf_2 GET** transaction.

The Compression Mechanism

To speed up transmission times, the RMX XML API provides an option that enables client applications to send HTTP XML strings to the MCU in compressed format, and to receive RMX XML strings from the MCU in compressed format. This is the recommended method of work for all XML strings that are larger than 10 KB.

Note To maintain backwards compatibility with the XAP, you can work with the RMX XML API without using compression. However, working with compression is strongly recommended.

Sending XML requests in Compressed Format

It is recommended that all XML request strings larger than 10 KB are compressed before being sent over the HTTP connection to the MCU.

To send an XML request string in compressed format:

Compress the XML string using the OpenSource **zlib** component.

Include the following header in the header file sent with the HTTP:

```
Content-Encoding: zip
```

Send the header file and compressed contents to the MCU.

Receiving XML responses from the MCU in Compressed Format

When you log in to an MCU, you can use the **COMPRESSION** element to specify whether or not you want to receive responses in compressed mode. If you request to receive responses in compressed mode, then all XML response strings that are larger than 10 KB will be sent over the HTTP to the client in compressed format. XML response strings that are smaller than 10 KB will not be compressed.

All compressed response strings will be sent with a header file which includes the following header:

```
Content-Encoding: zip
```

If the header file contains the header `Content-Encoding: zip`, then decompress the XML string using the OpenSource **zlib** component.

The **COMPRESSION** element

The **COMPRESSION** element is located in the **common_trans** schema and is an optional component of the **LOGIN** element in the **trans_mcu** schema. The **COMPRESSION** element is used to indicate whether or not responses should be compressed. By default there is no compression of responses.

The **COMPRESSION** element is defined as follows:

```
<xsd:element name="COMPRESSION" type="xsd:boolean"/>
```

The **LOGIN** element is defined as follows:

```
<xsd:element name="LOGIN" type="LoginRequestContent"/>
```

```
<xsd:complexType name="LoginRequestContent">
```

```
  <xsd:sequence>
```

```
    <xsd:element ref="MCU_IP"/>
```

```
    <xsd:element ref="USER_NAME"/>
```

```
    <xsd:element ref="PASSWORD"/>
```

```
    <xsd:element ref="STATION_NAME" minOccurs="0"/>
```

```
    <xsd:element ref="COMPRESSION" minOccurs="0"/>
```

```
    <xsd:element ref="CONFERENCE_RECORDER" minOccurs="0"/>
```

```
    <xsd:element ref="NEW_PASSWORD" minOccurs="0"/>
```

```
    <xsd:any namespace="##other" processContents="skip" minOccurs="0"
      maxOccurs="unbounded"/>
```

```
  </xsd:sequence>
```

```
</xsd:complexType>
```


The following is an example of the XML string needed to log in to the MCU when you want to receive all XML streams bigger than 10 KB in compressed mode:

```
<TRANS_MCU>
  <TRANS_COMMON_PARAMS>
    <MCU_TOKEN>0</MCU_TOKEN>
    <MCU_USER_TOKEN>0</MCU_USER_TOKEN>
    <ASync>
      <YOUR_TOKEN1>0</YOUR_TOKEN1>
      <YOUR_TOKEN2>0</YOUR_TOKEN2>
    </ASync>
    <MESSAGE_ID>0</MESSAGE_ID>
  </TRANS_COMMON_PARAMS>
  <ACTION>
    <LOGIN>
      <MCU_IP>
        <IP>127.0.0.1</IP>
        <LISTEN_PORT>80</LISTEN_PORT>
        <HOST_NAME/>
      </MCU_IP>
      <USER_NAME>POLYCOM</USER_NAME>
      <PASSWORD>POLYCOM</PASSWORD>
      <STATION_NAME>EMMA.F3-JUDITHS</STATION_NAME>
      <COMPRESSION>true</COMPRESSION>
    </LOGIN>
  </ACTION>
</TRANS_MCU>
```